

۱۲۳

A standard linear barcode is positioned vertically on the right side of the label. It consists of vertical black bars of varying widths on a white background.

	Subclass	ISSUE CLASSIFICATION

PATENT NUMBER

**U.S. UTILITY Patent Application**

 G.I.P.E. SCANNED	<b>G.I.P.E.</b> <b>Q.A.</b>	<b>PATENT DATE</b>
--	--------------------------------	--------------------

APPLICATION NO.	CONT/PRIOR	CLASS	SUBCLASS	ART UNIT	EXAMINER
09/767237		709	223	2151 2142	<i>Burgess</i> T. VII

CANTS

Cache management method and system for strong dynamic contents

三

PTO-2040  
12/99

## **ISSUING CLASSIFICATION**

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				<b>NOTICE OF ALLOWANCE MAILED</b>	
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____				<b>ISSUE FEE</b>	
				Amount Due	Date Paid
<input type="checkbox"/> The terminal _____ months of this patent have been disclaimed				<b>ISSUE BATCH NUMBER</b>	

**WARNING:**

**WARNING:** The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-436A  
(Rev. 6/99)

FILED WITH:  DISK (CRF)  FICHE  CD-ROM  
(Attached in pocket on right inside flap)

Best Available Copy